


**Rectus Series 1625KA - DN 7.8**

Rectus Tema premium European standard industrial coupling – the know-how from both brands combined in one system. Extremely robust 2-component plastic sleeve. Suitable for compressed air applications with above average air consumption.

**Advantages**

- Single handed operation
- High grade valve technology with optimum flow performance
- Minimum coupling forces

**Chart / Air**



**Working Pressure**

PB = 35 bar, maximum static working pressure with safety factor of 4 to 1.

**Working Temperature\***

-20°C up to +40°C (NBR) depending on the medium.  
\*At a temperature below -20°C and above +40°C special seals are available on request.

**Material**

**Coupling**

Back Body: Brass, Nickel Plated  
 Valve Body: Steel, QPQ treated  
 Sleeve: PA6 + TPE  
 Valve: Brass  
 Spring: AISI 301  
 Locking Ring and Locking Balls: AISI 420

**Seals**

NBR

**Plug**

Steel Hardened, Zinc Plated

**Coupling - Male Thread BSPT**

Thread A	Order code	Box Qty
3/8"	<b>1625KAAK17SPN_99</b>	10
1/2"	<b>1625KAAK21SPN_99</b>	10

**Plug - Male Thread BSPT**

Thread A	Order code	Box Qty
1/4"	<b>25SFAK13SXZ</b>	20
3/8"	<b>25SFAK17SXZ</b>	20
1/2"	<b>25SFAK21SXZ</b>	10

**Coupling - Female Thread BSPP**

Thread A	Order code	Box Qty
1/2"	<b>1625KAIW21SPN_99</b>	10

**Plug - Female Thread BSPP**

Thread A	Order code	Box Qty
1/4"	<b>25SFIW13SXZ</b>	20
3/8"	<b>25SFIW17SXZ</b>	20






PDE2600PNUK


# Parker One Pneumatic

Rectus

## Coupling - Hose Barb

	Thread A	Order code	Box Qty
	9 mm	<b>1625KATF09SPN_99</b>	10
	13 mm	<b>1625KATF13SPN_99</b>	10

## Plug - Hose Barb

	Thread A	Order code	Box Qty
	9 mm	<b>25SFTF09SXZ</b>	20
	13 mm	<b>25SFTF13SXZ</b>	20

